

WJT

Report No.: WJT190524-LVD-B-02

IU SMART CO.,LTD

LVD REPORT

Prepared For :	IU SMART CO.,LTD 808-809,8 FLOOR ZHANRUN internationgal, 33 longguan road, Longhua newdistrict, Shenzhen, Guangdong, China.	
Product Name:	Electric Scooter	
Model :	L2	
Prepared By:	Shenzhen WJT Technology Co., Ltd.	
Address:	3/F, Block A1, No. 5, 8th Road, Yangyong Industrial Park, Shapu Community, Songgang Street, Bao'an District, Shenzhen, China	
Test standard:	EN 60950-1:2006+A11:2009+A1:2010+A12:2011+A2:2013	
Test Date:	May 24, 2019 to May 28, 2019	
Date of Report :	May 28, 2019	
Report No.:	WJT190524-LVD-B-02	
Engineer:	Haney Honey 8	
Approved by:	Andy Approve	





LVD Report EN 60950-1

Information technology equipment - Safety -

Part 1: General requirements

Testing laboratory: Shenzhen WJT Technology Co., Ltd.

Address: 3/F, Block A1, No. 5, 8th Road, Yangyong Industrial Park, Shapu

Community, Songgang Street, Bao'an District, Shenzhen, China

Testing location: Shenzhen WJT Technology Co., Ltd.

Applicant: IU SMART CO.,LTD

Address : 808-809,8 FLOOR ZHANRUN internationgal , 33 longguan road ,

Longhua newdistrict , Shenzhen, Guangdong, China.

Standard : EN 60950-1:2006+A11:2009+A1:2010+ A12:2011+A2:2013

Test Result : Compliance with EN 60950-1:2006+A11:2009+A1:2010+A12:2011

+A2:2013

Procedure deviation: : /

Non-standard test method : /.

Type of test object Electric Scooter

Trademark: /

Model/type reference : L2

Rating: Input: 100-240V~, 50/60Hz, 2.5A

Output: 42.0V, 2.0A

Manufacturer : IU SMART CO.,LTD

Address : 808-809,8 FLOOR ZHANRUN internationgal , 33 longguan road ,

Longhua newdistrict , Shenzhen, Guangdong, China.

Test item particulars :

Equipment mobility : Direct plug-in equipment, Type A

Operation condition: Continuous Class of equipment: Class II

Protection against ingress of water : IP20

General information:

Electric Scooter, powered by mains, for indoor use only.

Both models are the same, except for different model names and appearances.

Tests were conducted on model L2 to represent the other model.



Page 3 of 55 Report No.: WJT190524-LVD-B-02

	Possible test case verdicts :			
	test case does not apply to the test object	N(.A.)		
	test object does meet the requirement	P(ass)		
	test object does not meet the requirement	F(ail)		
ı				

General remarks:	
"(see remark #)" refers to a remark appended to the	Attached with:
report.	A: photo documentation
"(see appended table)" refers to a table appended to the report.	
Throughout this report a comma is used as the decimal separator.	Remark:
The test results presented in this report relate only to the object tested.	
This report shall not be reproduced except in full without the written approval of the testing laboratory.	






Artwork of Marking Label:

Electric Scooter

Model: L2

Input: 100-240V~, 50/60Hz, 2.5A Output: 42.0V, 2.0A



IU SMART CO.,LTD

808-809,8 FLOOR ZHANRUN internationgal '33 longguan road 'Longhua

newdistrict, Shenzhen, Guangdong, China.

Importer:XXX Address: XXX

Made In China





	EN 60950-1		
Clause	Requirement + Test	Result - Remark	Verdict
1	GENERAL		Р
1.5	Components		Р
1.5.1	General		Р
	Comply with IEC 60950-1 or relevant component standard	(see appended tables 1.5.1)	Р
1.5.2	Evaluation and testing of components		Р
1.5.3	Thermal controls		N/A
1.5.4	Transformers		Р
1.5.5	Interconnecting cables		Р
1.5.6	Capacitors bridging insulation	Y capacitor used.	Р
1.5.7	Resistors bridging insulation	No such resistors	N/A
1.5.7.1	Resistors bridging functional, basic or supplementary insulation		N/A
1.5.7.2	Resistors bridging double or reinforced insulation between a.c. mains and other circuits	No such resistors	N/A
1.5.7.3	Resistors bridging double or reinforced insulation between a.c. mains and antenna or coaxial cable	No such resistors	N/A
1.5.8	Components in equipment for IT power systems	Not intended for IT power systems	N/A
1.5.9	Surge suppressors		N/A
1.5.9.1	General		N/A
1.5.9.2	Protection of VDRs		N/A
1.5.9.3	Bridging of functional insulation by a VDR		N/A
1.5.9.4	Bridging of basic insulation by a VDR		N/A
1.5.9.5	Bridging of supplementary, double or reinforced insulation by a VDR		N/A
1.6	Power Interface		Р
1.6.1	AC power distribution systems		Р
1.6.2	Input current		Р
1.6.3	Voltage limit of hand-held equipment	The equipment is not handheld.	N/A
1.6.4	Neutral conductor	Considering the neutral conductor was live conductor, the neutral conductor was insulated from the body with reinforced insulation throughout the equipment.	Р
1.7	Marking and Instructions		P





EN 60950-1				
Clause	Requirement + Test	Result - Remark	Verdict	
1.7.1	Power rating and identification markings	The required marking is located on the outside surface of the equipment	Р	
1.7.1.1	Power rating marking	See below	Р	
	Multiple mains supply connections		N/A	
	Rated voltage(s) or voltage range(s) (V)	100-240V~	Р	
	Symbol for nature of supply, for d.c. only	The equipment is for a.c. supply	N/A	
	Rated frequency or rated frequency range (Hz)	50/60Hz	Р	
	Rated current (mA or A)		Р	
1.7.1.2	Identification markings		Р	
	Manufacturer's name or trade-mark or identification mark	See page 1	Р	
	Model identification or type reference	See page 1	Р	
	Symbol for Class II equipment only	symbol used.	Р	
	Other markings and symbols	The additional marking does not give rise to misunderstandings.	Р	
1.7.2	Safety instructions and marking	Operating/safety instructions made available to the user.	Р	
1.7.2.1	General		Р	
1.7.2.2	Disconnect devices	Plug used	Р	
1.7.2.3	Overcurrent protective device	Plug used	N/A	
1.7.2.4	IT power distribution systems		N/A	
1.7.2.5	Operator access with a tool	All areas containing hazard(s) are inaccessible to the operator.	Р	
1.2.7.6	Ozone	Not such equipment.	N/A	
1.7.3	Short duty cycles	Equipment is designed for continuous operation.	N/A	
1.7.4	Supply voltage adjustment	No voltage selector.	N/A	
	Methods and means of adjustment; reference to installation instructions		N/A	
1.7.5	Power outlets on the equipment		N/A	
1.7.6	Fuse identification (marking, special fusing characteristics, cross-reference)	Fuse resistor used	Р	
1.7.7	Wiring terminals		Р	
1.7.7.1	Protective earthing and bonding terminals		N/A	
1.7.7.2	Terminals for a.c. mains supply conductors	The equipment is not permanently connected or provided with a plug.	Р	
1.7.7.3	Terminals for d.c. mains supply conductors		N/A	





	EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict	
1.7.8	Controls and indicators		N/A	
1.7.8.1	Identification, location and marking		N/A	
1.7.8.2	Colours		N/A	
1.7.8.3	Symbols according to IEC 60417		N/A	
1.7.8.4	Markings using figures	No figures used	N/A	
1.7.9	Isolation of multiple power sources	Only one connection supplying hazardous voltagess and energy levels to the equipment.	N/A	
1.7.10	Thermostats and other regulating devices	No such regulating devices.	N/A	
1.7.11	Durability		Р	
1.7.12	Removable parts	No removable part.	N/A	
1.7.13	Replaceable batteries	No battery provided.	N/A	
	Language(s)	English	_	
1.7.14	Equipment for restricted access locations	Not intended for use in restricted access locations.	N/A	
2	PROTECTION FROM HAZARDS		Р	
2.1	Protection from electric shock and energy hazards		Р	
2.1.1	Protection in operator access areas		Р	
2.1.1.1	Access to energized parts		Р	
	Test by inspection	No openings available except for hole for output terminal	Р	
	Test with test finger (Figure 2A)		Р	
	Test with test pin (Figure 2B)		Р	
	Test with test probe (Figure 2C)		N/A	
2.1.1.2	Battery compartments	No battery compartments	N/A	
2.1.1.3	Access to ELV wiring	No ELV circuit	N/A	
	Working voltage (Vpeak or Vrms); minimum distance through insulation (mm)			
2.1.1.4	Access to hazardous voltage circuit wiring		N/A	
2.1.1.5	Energy hazards	The energy does not exceed 240VA between any two points in output connectors. See appended table 2.1.1.5	Р	
2.1.1.6	Manual controls	No such device	N/A	
2.1.1.7	Discharge of capacitors in equipment		N/A	
	Measured voltage (V); time-constant (s)		_	
2.1.1.8	Energy hazards – d.c. mains supply		N/A	
	a) Capacitor connected to the d.c. mains supply		N/A	





	EN 60950-1				
Clause	Requirement + Test	Result - Remark	Verdict		
	b) Internal battery connected to the d.c. mains supply		N/A		
2.1.1.9	Audio amplifiers		N/A		
2.1.2	Protection in service access areas	No service access area.	N/A		
2.1.3	Protection in restricted access locations	The unit is not limited to be used in restricted access locations	N/A		
2.2	SELV Circuits		Р		
2.2.1	General requirements		Р		
2.2.2	Voltages under normal conditions (V)	T1 Secondary Output: 42V	Р		
2.2.3	Voltages under fault conditions (V)	Fault conditon: 0V	Р		
2.2.4	Connection of SELV circuits to other circuits		N/A		
2.3	TNV Circuits		N/A		
2.3.1	Limits		N/A		
	Type of TNV circuits		N/A		
2.3.2	Separation from other circuits and from accessible parts		N/A		
2.3.2.1	General requirements		N/A		
2.3.2.2	Protection by basic insulation		N/A		
2.3.2.3	Protection by earthing		N/A		
2.3.2.4	Protection by other constructions		N/A		
2.3.3	Separation from hazardous voltages		N/A		
	Insulation employed		_		
2.3.4	Connection of TNV circuits to other circuits		N/A		
	Insulation employed		_		
2.3.5	Test for operating voltages generated externally		N/A		
2.4	Limited current circuits		Р		
2.4.1	General requirements		Р		
2.4.2	Limit values	35.84mA	Р		
	Frequency (Hz)	51.2kHz	_		
	Measured current (mA)	11.9mA	_		
	Measured voltage (V)	23.8V	_		
	Measured circuit capacitance (nF or µF)		_		
2.4.3	Connection of limited current circuits to other circuits		N/A		





	EN 60950-1		
Clause	Requirement + Test	Result - Remark	Verdict
2.5	Limited Power Sources		Р
	a) Inherently limited output		Р
	b) Impedance limited output		N/A
	c) Regulating network limited output under normal operating and single fault condition		N/A
	d) Overcurrent protective device limited output		N/A
	Max. output voltage (V), max. output current (A), max. apparent power (VA)	For cord outptut: Uoc=5.11V, Isc=2.37A,VA=9.32.	_
	Current rating of overcurrent protective device (A)		_
	Use of integrated circuit (IC) current limiters		N/A
2.6	Provisions for Earthing and Bonding		N/A
2.6.1	Protective earthing		N/A
2.6.2	Functional earthing		N/A
2.6.3	Protective earthing and protective bonding conductors		N/A
2.6.3.1	General		N/A
2.6.3.2	Size of protective earthing conductors		NI/A

2.0	1 Tovisions for Euramig and Bonding	IVA
2.6.1	Protective earthing	N/A
2.6.2	Functional earthing	N/A
2.6.3	Protective earthing and protective bonding conductors	N/A
2.6.3.1	General	N/A
2.6.3.2	Size of protective earthing conductors	N/A
	Rated current (A), cross-sectional area (mm²), AWG	_
2.6.3.3	Size of protective bonding conductors	N/A
	Rated current (A), cross-sectional area (mm²), AWG	_
	Protective current rating (A), cross-sectional area (mm²), AWG	_
2.6.3.4	Resistance of earthing conductors and their terminations; resistance (Ω) , voltage drop (V) , test current (A) , duration (min)	N/A
2.6.3.5	Colour of insulation	N/A
2.6.4	Terminals	N/A
2.6.4.1	General	N/A
2.6.4.2	Protective earthing and bonding terminals	N/A
	Rated current (A), type, nominal thread diameter (mm)	_
2.6.4.3	Separation of the protective earthing conductor from protective bonding conductors	N/A
2.6.5	Integrity of protective earthing	N/A
2.6.5.1	Interconnection of equipment	N/A





2.6.5.6

2.6.5.7

2.6.5.8

Corrosion resistance

Screws for protective bonding

cable distribution system

Reliance on telecommunication network or

EN 60950-1 Clause Requirement + Test Result - Remark Verdict 2.6.5.2 Components in protective earthing conductors N/A and protective bonding conductors 2.6.5.3 Disconnection of protective earth N/A N/A 2.6.5.4 Parts that can be removed by an operator N/A 2.6.5.5 Parts removed during servicing

Report No.: WJT190524-LVD-B-02

N/A

N/A

N/A

2.7	Overcurrent and Earth Fault Protection in Primary Circuits		P
2.1	Overcurrent and Earth Fault Protection in Prin	nary Circuits	P
2.7.1	Basic requirements	The equipment relies on rated fuse resistor.	Р
	Instructions when protection relies on building installation		Р
2.7.2	Faults not simulated in 5.3.7		Р
2.7.3	Short-circuit backup protection		Р
2.7.4	Number and location of protective devices	One fuse resistor located at PCB board	Р
2.7.5	Protection by several devices		N/A
2.7.6	Warning to service personnel		N/A

2.8 Safety Interlocks			N/A
2.8.1	General principles	No safety interlocks used	N/A
2.8.2	Protection requirements		N/A
2.8.3	Inadvertent reactivation		N/A
2.8.4	Fail-safe operation		N/A
	Protection against extreme hazard		N/A
2.8.5	Moving parts		N/A
2.8.6	Overriding		N/A
2.8.7	Switches, relays and their related circuits		N/A
2.8.7.1	Separation distances for contact gaps and their related circuits (mm)		N/A
2.8.7.2	Overload test		N/A
2.8.7.3	Endurance test		N/A
2.8.7.4	Electric strength test		N/A
2.8.8	Mechanical actuators		N/A




Page 11 of 55

Report No.: WJT190524-LVD-B-02

	EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict	

2.9	Electrical Insulation		Р
2.9.1	Properties of insulating materials	Suitable material according to their thermal electrical and mechanical properties.	Р
2.9.2	Humidity conditioning		Р
	Relative humidity (%), temperature (°C)	93 %RH, 25 °C, 48 h	
2.9.3	Grade of insulation	The adequate levels of safety insulation is provided and maintained to comply with the requirements of this standard	Р
2.9.4	Separation from hazardous voltages		Р
	Method(s) used		_

2.10	Clearances, Creepage Distances and Distance	es Through Insulation	P
2.10.1	General		Р
2.10.1.1	Frequency		Р
2.10.1.2	Pollution degrees	Pollution degree 2	Р
2.10.1.3	Reduced values for functional insulation		N/A
2.10.1.4	Intervening unconnected conductive parts		N/A
2.10.1.5	Insulation with varying dimensions	No such transfomer used.	N/A
2.10.1.6	Special separation requirements	Special separation is not used.	N/A
2.10.1.7	Insulation in circuits generating starting pulses	The circuit will not generate starting pulse	N/A
2.10.2	Determination of working voltage		Р
2.10.2.1	General		Р
2.10.2.2	RMS working voltage		Р
2.10.2.3	Peak working voltage		Р
2.10.3	Clearances		Р
2.10.3.1	General		N/A
2.10.3.2	Mains transient voltages		N/A
	a) AC mains supply		N/A
	b) Earthed d.c. mains supplies		N/A
	c) Unearthed d.c. mains supplies		N/A
	d) Battery operation		N/A
2.10.3.3	Clearances in primary circuits		Р
2.10.3.4	Clearances in secondary circuits	Only the functional insulation in	N/A





	EN 60950-1		
Clause	Requirement + Test	Result - Remark	Verdict
		secondary circuits complied with clause 5.3.4	
2.10.3.5	Clearances in circuits having starting pulses	The circuit will not generate starting pulse.	N/A
2.10.3.6	Transients from a.c. mains supply		N/A
2.10.3.7	Transients from d.c. mains supply	Not connected to d.c mains supply.	N/A
2.10.3.8	Transients from telecommunication networks and cable distribution systems		N/A
2.10.3.9	Measurement of transient voltage levels		N/A
	a) Transients from a mains supply		N/A
	For an a.c. mains supply		N/A
	For a d.c. mains supply		N/A
	b) Transients from a telecommunication network :		N/A
2.10.4	Creepage distances		Р
2.10.4.1	General		Р
2.10.4.2	Material group and comparative tracking index		Р
	CTI tests	Material group IIIb is assumed to be used	_
2.10.4.3	Minimum creepage distances		Р
2.10.5	Solid insulation		Р
2.10.5.1	General		Р
2.10.5.2	Distances through insulation		Р
2.10.5.3	Insulating compound as solid insulation	For optocouplers, see appended table 1.5.1.	Р
2.10.5.4	Semiconductor devices	For optocouplers, see appended table 1.5.1.	Р
2.10.5.5.	Cemented joints		N/A
2.10.5.6	Thin sheet material – General		N/A
2.10.5.7	Separable thin sheet material		N/A
	Number of layers (pcs)		_
2.10.5.8	Non-separable thin sheet material		N/A
2.10.5.9	Thin sheet material – standard test procedure		N/A
	Electric strength test		_
2.10.5.10	Thin sheet material – alternative test procedure		Р
	Electric strength test		_





	EN 60950-1		
Clause	Requirement + Test	Result - Remark	Verdict
2.10.5.11	Insulation in wound components		Р
2.10.5.12	Wire in wound components		Р
	Working voltage		Р
	a) Basic insulation not under stress		Р
	b) Basic, supplementary, reinforced insulation		Р
	c) Compliance with Annex U		Р
	Two wires in contact inside wound component; angle between 45° and 90°		Р
2.10.5.13	Wire with solvent-based enamel in wound components		N/A
	Electric strength test		
	Routine test		N/A
2.10.5.14	Additional insulation in wound components		N/A
	Working voltage		N/A
	- Basic insulation not under stress		N/A
	- Supplementary, reinforced insulation		N/A
2.10.6	Construction of printed boards		Р
2.10.6.1	Uncoated printed boards		Р
2.10.6.2	Coated printed boards	No special coating in order to reduce distances.	N/A
2.10.6.3	Insulation between conductors on the same inner surface of a printed board		N/A
2.10.6.4	Insulation between conductors on different layers of a printed board		N/A
	Distance through insulation		N/A
	Number of insulation layers (pcs)		N/A
2.10.7	Component external terminations		Р
2.10.8	Tests on coated printed boards and coated components		N/A
2.10.8.1	Sample preparation and preliminary inspection		N/A
2.10.8.2	Thermal conditioning		N/A
2.10.8.3	Electric strength test		N/A
2.10.8.4	Abrasion resistance test		N/A
2.10.9	Thermal cycling		N/A
2.10.10	Test for Pollution Degree 1 environment and insulating compound		N/A
2.10.11	Tests for semiconductor devices and cemented		N/A



Termination of conductors

10 N pull test

Sleeving on wiring

Page 14 of 55 Report No.: WJT190524-LVD-B-02

EN 60950-1 Clause Requirement + Test Result - Remark Verdict joints 2.10.12 N/A Enclosed and sealed parts 3 WIRING, CONNECTIONS AND SUPPLY Ρ 3.1 General Р 3.1.1 Current rating and overcurrent protection Р 3.1.2 Р Protection against mechanical damage Wire does not touch sharp edges which could damage the insulation and cause hazard. Р 3.1.3 Securing of internal wiring Internal wiring is secured against excessive strain, loosening of terminals and damage to the conductor insulation. Р 3.1.4 Insulation of conductors Insulation on internal conductors is considered to be of adequate quality and suitable for the application and the working voltage involved. 3.1.5 N/A Beads and ceramic insulators 3.1.6 Screws for electrical contact pressure N/A 3.1.7 N/A Insulating materials in electrical connections No contact pressure through insulating material. 3.1.8 Self-tapping and spaced thread screws N/A

3.2	Connection to A Mains Supply		P
3.2.1	Means of connection		Р
3.2.1.1	Connection to an a.c. mains supply	Plug used	Р
3.2.1.2	Connection to a d.c. mains supply	Not for connection to a d.c mains supply	N/A
3.2.2	Multiple supply connections	Only one supply connection.	N/A
3.2.3	Permanently connected equipment	The equipment is not intended for permanent connection to the mains.	N/A
	Number of conductors, diameter of cable and conduits (mm)		_

Р

Ρ

N/A

Terminations cannot become displaced so that clearances and creepage distances can

be reduced.

Shenzhen WJT Technology Co., Ltd. Website: http://www.wjt-test.com

3.1.9

3.1.10





	EN 60950-1	T	1
Clause	Requirement + Test	Result - Remark	Verdict
3.2.4	Appliance inlets		N/A
3.2.5	Power supply cords		N/A
3.2.5.1	AC power supply cords		N/A
	Type		_
	Rated current (A), cross-sectional area (mm²), AWG		_
3.2.5.2	DC power supply cords		N/A
3.2.6	Cord anchorages and strain relief	Plug used	N/A
	Mass of equipment (kg), pull (N)		_
	Longitudinal displacement (mm)		_
3.2.7	Protection against mechanical damage		N/A
3.2.8	Cord guards		N/A
	Diameter or minor dimension D (mm); test mass (g)		_
	Radius of curvature of cord (mm)		
3.2.9	Supply wiring space		N/A
3.3	Wiring Terminals for Connection of External Conductors		N/A
3.3.1	Wiring terminals		N/A
3.3.2	Connection of non-detachable power supply cords		N/A
3.3.3	Screw terminals		N/A
3.3.4	Conductor sizes to be connected		N/A
	Rated current (A), cord/cable type, cross-sectional area (mm²)		_
3.3.5	Wiring terminal sizes		N/A
	Rated current (A), type, nominal thread diameter (mm)		_
3.3.6	Wiring terminal design		N/A
3.3.7	Grouping of wiring terminals		N/A
3.3.8	Stranded wire		N/A
3.4	Disconnection from the Mains Supply		Р
3.4.1	General requirement		Р
3.4.2	Disconnect devices		Р
3.4.3	Permanently connected equipment	Not permanently connected equipment.	N/A



Page 16 of 55 Report No.: WJT190524-LVD-B-02

	EN 60950-1		
Clause	Requirement + Test	Result - Remark	Verdict
3.4.4	Parts which remain energized	No parts remain energized	N/A
	J T	after the disconnect device.	1071
3.4.5	Switches in flexible cords	No isolating switch in the cord set.	N/A
3.4.6	Number of poles - single-phase and d.c. equipment	Disconnect both poles simultaneously	Р
3.4.7	Number of poles - three-phase equipment	Single phase	N/A
3.4.8	Switches as disconnect devices	There is no switch acting as disconnect devices	N/A
3.4.9	Plugs as disconnect devices		Р
3.4.10	Interconnected equipment	No interconnection of hazardous voltages.	N/A
3.4.11	Multiple power sources	One power source only.	N/A
3.5	Interconnection of Equipment		Р
3.5.1	General requirements		Р
3.5.2	Types of interconnection circuits		Р
3.5.3	ELV circuits as interconnection circuits		N/A
3.5.4	Data ports for additional equipment		Р
4	PHYSICAL REQUIREMENTS		Р
4.1	Stability		N/A
	Angle of 10°		N/A
	Test force (N)		N/A
4.2	Mechanical Strength		Р
4.2.1	General	Complies with the requirement also after tests described below are applied	Р
	Rack-mounted equipment.	No rack-mounted equipment.	N/A
4.2.2	Steady force test, 10 N		Р
4.2.3	Steady force test, 30 N	No internal enclosure.	N/A
4.2.4	Steady force test, 250 N	No hazard. The test is performed at all sources of plastic enclosure.	Р
4.2.5	Impact test		N/A

Fall test

Swing test





EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
4.2.6	Drop test; height (mm)	1000mm, 3 times	Р
4.2.7	Stress relief test	Test is carried out at 84°C / 7hrs. No risk of shrinkage or distortion on enclosures due to release of internal stresses.	Р
4.2.8	Cathode ray tubes	No CRT provided.	N/A
	Picture tube separately certified		N/A
4.2.9	High pressure lamps	No high pressure lamps in the equipment.	N/A
4.2.10	Wall or ceiling mounted equipment; force (N)	Not intended to be mounted on a wall or ceiling.	N/A
4.2.11	Rotating solid media		N/A
	Test to cover on the door:		N/A

4.3	Design and Construction		Р
4.3.1	Edges and corners	All edges and corners are rounded and /or smoothed.	Р
4.3.2	Handles and manual controls; force (N)	No knobs, grips, handles, lever etc.	N/A
4.3.3	Adjustable controls	No hazardous adjustable controls.	N/A
4.3.4	Securing of parts	No loosening of parts impairing creepage distances or clearances is likely to occur.	Р
4.3.5	Connection by plugs and sockets		N/A
4.3.6	Direct plug-in equipment		N/A
	Torque		_
	Compliance with the relevant mains plug standard		N/A
4.3.7	Heating elements in earthed equipment	No heating elements	N/A
4.3.8	Batteries	No battery use	N/A
	- Overcharging of a rechargeable battery		N/A
	- Unintentional charging of a non-rechargeable battery		N/A
	- Reverse charging of a rechargeable battery		N/A
	- Excessive discharging rate for any battery		N/A
4.3.9	Oil and grease	No oil and grease	N/A
4.3.10	Dust, powders, liquids and gases	No Dust, powders, liquids and gases	N/A





N/A

N/A

	EN 60950-1		
Clause	Requirement + Test	Result - Remark	Verdict
4.3.11	Containers for liquids or gases	No Containers for liquids or gases	N/A
4.3.12	Flammable liquids	No flammable liquids	N/A
	Quantity of liquid (I)		N/A
	Flash point (°C)		N/A
4.3.13	Radiation		Р
4.3.13.1	General		Р
4.3.13.2	Ionizing radiation		N/A
	Measured radiation (pA/kg)		_
	Measured high-voltage (kV)		_
	Measured focus voltage (kV)		_
	CRT markings		_
4.3.13.3	Effect of ultraviolet (UV) radiation on materials		N/A
	Part, property, retention after test, flammability classification		N/A
4.3.13.4	Human exposure to ultraviolet (UV) radiation		N/A
4.3.13.5	Lasers (including laser diodes) and LEDs		N/A
4.3.13.5. 1	Lasers (including laser diodes)		N/A
	Laser class		_
4.3.13.5. 2	Light emitting diodes (LEDs)		N/A
4.3.13.6	Other types		N/A
4.4	Protection against hazardous moving parts		N/A
4.4.1	General		N/A
4.4.2	Protection in operator access areas		N/A
	Household and home/office document/media shredders		N/A
4.4.3	Protection in restricted access locations		N/A
4.4.4	Protection in service access areas		N/A
4.4.5	Protection against moving fan blades		N/A
4.4.5.1	General		N/A
	Not considered to cause pain or injury.		N/A

Shenzhen WJT Technology Co., Ltd. Website: http://www.wjt-test.com

a)....:

b)

Is considered to cause pain, not injury.

Considered to cause injury.





EN 60950-1 Clause Requirement + Test Result - Remark Verdict c) 4.4.5.2 Protection for users N/A Use of symbol or N/A warning: 4.4.5.3 Protection for service persons N/A Use of symbol or N/A warning:

Report No.: WJT190524-LVD-B-02

4.5	Thermal Requirements		Р
4.5.1	General		Р
4.5.2	Temperature tests		Р
	Normal load condition per Annex L		_
4.5.3	Temperature limits for materials	(see appended table 4.5)	Р
4.5.4	Touch temperature limits	(see appended table 4.5)	Р
4.5.5	Resistance to abnormal heat		Р

4.6	Openings in Enclosures	N/A
4.6.1	Top and side openings	N/A
	Dimensions (mm)	_
4.6.2	Bottoms of fire enclosures	N/A
	Construction of the bottomm, dimensions (mm)	_
4.6.3	Doors or covers in fire enclosures	N/A
4.6.4	Openings in transportable equipment	N/A
4.6.4.1	Constructional design measures	N/A
	Dimensions (mm)	_
4.6.4.2	Evaluation measures for larger openings	N/A
4.6.4.3	Use of metallized parts	N/A
4.6.5	Adhesives for constructional purposes	N/A
	Conditioning temperature (°C), time (weeks):	_

4.7	Resistance to Fire		Р
4.7.1	Reducing the risk of ignition and spread of flame	Use of materials with the required flammability classes.	Р
	Method 1, selection and application of components wiring and materials	See appended table 1.5.1	Р
	Method 2, application of all of simulated fault condition tests		Р





EN 60950-1				
Clause	Requirement + Test	Result - Remark	Verdict	
4.7.2	Conditions for a fire enclosure		Р	
4.7.2.1	Parts requiring a fire enclosure	The fire enclosure is required.	Р	
4.7.2.2	Parts not requiring a fire enclosure		N/A	
4.7.3	Materials	,	Р	
4.7.3.1	General	Parts mounted on PCB of flammability class V-1 or better.	Р	
4.7.3.2	Materials for fire enclosures	Plastic enclosure: Min.V-1	Р	
4.7.3.3	Materials for components and other parts outside fire enclosures	No part outside fire enclosure.	Р	
4.7.3.4	Materials for components and other parts inside fire enclosures	Internal components except small parts are V-2 or better.	Р	
4.7.3.5	Materials for air filter assemblies	No air filters provided.	N/A	
4.7.3.6	Materials used in high-voltage components	No high voltage components provided.	N/A	

5	ELECTRICAL REQUIREMENTS AND SIMULAT CONDITIONS	TED ABNORMAL	Р
5.1	Touch current and protective conductor curre	ent	Р
5.1.1	General	Test conducted in accordance with 5.1.2 to 5.1.7.	Р
5.1.2	Configuration of equipment under test (EUT)		Р
5.1.2.1	Single connection to an a.c. mains supply		Р
5.1.2.2	Redundant multiple connections to an a.c. mains supply		N/A
5.1.2.3	Simultaneous multiple connections to an a.c. mains supply		Р
5.1.3	Test circuit		Р
5.1.4	Application of measuring instrument	Using measuring instrument in annex D.	Р
5.1.5	Test procedure		Р
5.1.6	Test measurements		Р
	Supply voltage (V)	264V	_
	Measured touch current (mA)	0.21	_
	Max. allowed touch current (mA)	0.25	_
	Measured protective conductor current (mA)		_
	Max. allowed protective conductor current (mA)		_
5.1.7	Equipment with touch current exceeding 3,5 mA		N/A
5.1.7.1	General		N/A





EN 60950-1				
Clause	Requirement + Test	Result - Remark	Verdict	
5.1.7.2	Simultaneous multiple connections to the supply		N/A	
5.1.8	Touch currents to telecommunication networks and cable distribution systems and from telecommunication networks		N/A	
5.1.8.1	Limitation of the touch current to a telecommunication network or to a cable distribution system		N/A	
	Supply voltage (V)			
	Measured touch current (mA)			
	Max. allowed touch current (mA)			
5.1.8.2	Summation of touch currents from telecommunication networks		N/A	
	a) EUT with earthed telecommunication ports		N/A	
	b) EUT whose telecommunication ports have no reference to protective earth		N/A	
5.2	Electric Strength		Р	
5.2.1	General		Р	
5.2.2	Test procedure		Р	
5.3	Abnormal Operating and Fault Conditions		Р	
5.3.1	Protection against overload and abnormal operation		Р	
5.3.2	Motors		N/A	
5.3.3	Transformers	(see appended Annex C and table 5.3)	Р	
5.3.4	Functional insulation	Method c). Test results see appended table 5.3.	Р	
5.3.5	Electromechanical components		N/A	
5.3.6	Audio amplifiers in ITE		N/A	
5.3.7	Simulation of faults		Р	
5.3.8	Unattended equipment		N/A	
5.3.9	Compliance criteria for abnormal operating and fault conditions		Р	
5.3.9.1	During the tests		Р	
5.3.9.2	After the tests		Р	
	CONNECTION TO THE ECOMMUNICATION NE		NI/A	

6	CONNECTION TO TELECOMMUNICATION NETWORKS	N/A
6.1	Protection of telecommunication network service persons, and users of other equipment connected to the network, from hazards in the equipment	N/A





Report No.: WJT190524-LVD-B-02 EN 60950-1 Clause Requirement + Test Result - Remark Verdict 6.1.1 Protection from hazardous voltages N/A 6.1.2 Separation of the telecommunication network from earth N/A 6.1.2.1 Requirements N/A Supply voltage (V) Current in the test circuit (mA) 6.1.2.2 Exclusions N/A 6.2 Protection of Equipment Users from Overvoltages on Telecommunication N/A **Networks** 6.2.1 Separation requirements N/A 6.2.2 Electric strength test procedure N/A 6.2.2.1 Impulse test N/A 6.2.2.2 Steady-state test N/A 6.2.2.3 Compliance criteria N/A 6.3 Protection of the telecommunication wiring system from overheating N/A Max. output current (A) Current limiting method

7	CONNECTION TO CABLE DISTRIBUTION SYSTEMS	N/A
7.1	General	N/A
7.2	Protection of cable distribution system service persons, and users of other equipment connected to the system, from hazardous voltages in the equipment	N/A
7.3	Protection of equipment users from overvoltages on the cable distribution system	N/A
7.4	Insulation between primary circuits and cable distribution systems	N/A
7.4.1	General	N/A
7.4.2	Voltage surge test	N/A
7.4.3	Impulse test	N/A

A	ANNEX A, TESTS FOR RESISTANCE TO HEAT AND FIRE	Р
A.1	Flammability test for fire enclosures of movable equipment having a total mass exceeding 18 kg, and of stationary equipment (see 4.7.3.2)	N/A
A.1.1	Samples	_





EN 60950-1				
Clause	Requirement + Test Requirement + Test	esult - Remark	Verdict	
	Wall thickness (mm)		_	
A.1.2	Conditioning of samples; temperature (°C)		N/A	
A.1.3	Mounting of samples		N/A	
A.1.4	Test flame (see IEC 60695-11-3)		N/A	
	Flame A, B, C or D			
A.1.5	Test procedure		N/A	
A.1.6	Compliance criteria		N/A	
	Sample 1 burning time (s)			
	Sample 2 burning time (s)		_	
	Sample 3 burning time (s)		_	
A.2	Flammability test for fire enclosures of movable equ not exceeding 18 kg, and for material and compone enclosures (see 4.7.3.2 and 4.7.3.4)		N/A	
A.2.1	Samples, material			
	Wall thickness (mm)		_	
A.2.2	Conditioning of samples; temperature (°C)		N/A	
A.2.3	Mounting of samples		N/A	
A.2.4	Test flame (see IEC 60695-11-4)		N/A	
	Flame A, B or C		_	
A.2.5	Test procedure		Р	
A.2.6	Compliance criteria		Р	
	Sample 1 burning time (s)		_	
	Sample 2 burning time (s)			
	Sample 3 burning time (s)			
A.2.7	Alternative test acc. to IEC 60695-11-5, cl. 5 and 9		N/A	
	Sample 1 burning time (s)		_	
	Sample 2 burning time (s)		_	
	Sample 3 burning time (s)		_	
A.3	Hot flaming oil test (see 4.6.2)		N/A	
A.3.1	Mounting of samples		N/A	
A.3.2	Test procedure		N/A	
A.3.3	Compliance criterion		N/A	
В	ANNEX B, MOTOR TESTS UNDER ABNORMAL (CONDITIONS (ago 4.7.2.2	N/A	



Page 24 of 55

Report No.: WJT190524-LVD-B-02

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	and 5.3.2)		
B.1	General requirements		N/A
	Position		_
	Manufacturer		_
	Type		_
	Rated values		_
B.2	Test conditions		N/A
B.3	Maximum temperatures		N/A
B.4	Running overload test		N/A
B.5	Locked-rotor overload test		N/A
	Test duration (days)		_
	Electric strength test: test voltage (V)		_
B.6	Running overload test for d.c. motors in secondary circuits		N/A
B.6.1	General		N/A
B.6.2	Test procedure		N/A
B.6.3	Alternative test procedure		N/A
B.6.4	Electric strength test; test voltage (V)		N/A
B.7	Locked-rotor overload test for d.c. motors in secondary circuits		N/A
B.7.1	General		N/A
B.7.2	Test procedure		N/A
B.7.3	Alternative test procedure		N/A
B.7.4	Electric strength test; test voltage (V)		N/A
B.8	Test for motors with capacitors		N/A
B.9	Test for three-phase motors		N/A
B.10	Test for series motors		N/A
	Operating voltage (V)		_
С	ANNEX C, TRANSFORMERS (see 1.5.4 and 5.	3.3)	P
	Position	. T1	_
	Manufacturer		_
	Type	+	_
	Rated values		_





EN 60950-1 Clause Requirement + Test Result - Remark Verdict C.1 Overload test Inherent Р C.2 Insulation Ρ Р Protection from displacement of windings By bobbin and insulation tape D P ANNEX D, MEASURING INSTRUMENTS FOR TOUCH-CURRENT TESTS (see 5.1.4) D.1 Measuring instrument Ρ D.2 Alternative measuring instrument Р E ANNEX E, TEMPERATURE RISE OF A WINDING (see 1.4.13) N/A F ANNEX F, MEASUREMENT OF CLEARANCES AND CREEPAGE Ρ **DISTANCES** (see 2.10 and Annex G)

	DIOTARGEO (SGC 2:10 dila Almox O)	
G	ANNEX G, ALTERNATIVE METHOD FOR DETERMINING MINIMUM CLEARANCES	N/A
G.1	Clearances	N/A
G.1.1	General	N/A
G.1.2	Summary of the procedure for determining minimum clearances	N/A
G.2	Determination of mains transient voltage (V)	N/A
G.2.1	AC mains supply	N/A
G.2.2	Earthed d.c. mains supplies	N/A
G.2.3	Unearthed d.c. mains supplies	N/A
G.2.4	Battery operation	N/A
G.3	Determination of telecommunication network transient voltage (V)	N/A
G.4	Determination of required withstand voltage (V)	N/A
G.4.1	Mains transients and internal repetitive peaks	N/A
G.4.2	Transients from telecommunication networks	N/A
G.4.3	Combination of transients	N/A
G.4.4	Transients from cable distribution systems	N/A
G.5	Measurement of transient voltages (V)	N/A
	a) Transients from a mains supply	N/A
	For an a.c. mains supply	N/A
	For a d.c. mains supply	N/A
	b) Transients from a telecommunication network	N/A





	EN 60950-1	
Clause	Requirement + Test Result - Remark	Verdict
G.6	Determination of minimum clearances	N/A
н	ANNEX H, IONIZING RADIATION (see 4.3.13)	N/A
J	ANNEX J, TABLE OF ELECTROCHEMICAL POTENTIALS (see 2.6.5.6)	N/A
	Metal(s) used	_
K	ANNEX K, THERMAL CONTROLS (see 1.5.3 and 5.3.8)	N/A
K.1	Making and breaking capacity	N/A
K.2	Thermostat reliability; operating voltage (V)	N/A
K.3	Thermostat endurance test; operating voltage (V)	N/A
K.4	Temperature limiter endurance; operating voltage (V)	N/A
K.5	Thermal cut-out reliability	N/A
K.6	Stability of operation	N/A
L	ANNEX L, NORMAL LOAD CONDITIONS FOR SOME TYPES OF ELECTRICAL BUSINESS EQUIPMENT (see 1.2.2.1 and 4.5.2)	N/A
L.1	Typewriters	N/A
L.2	Adding machines and cash registers	N/A
L.3	Erasers	N/A
L.4	Pencil sharpeners	N/A
L.5	Duplicators and copy machines	N/A
L.6	Motor-operated files	N/A
L.7	Other business equipment	Р
M	ANNEX M, CRITERIA FOR TELEPHONE RINGING SIGNALS (see 2.3.1)	N/A
M.1	Introduction	N/A
M.2	Method A	N/A
M.3	Method B	N/A
M.3.1	Ringing signal	N/A
M.3.1.1	Frequency (Hz)	_
M.3.1.2	Voltage (V)	_
M.3.1.3	Cadence; time (s), voltage (V)	
M.3.1.4	Single fault current (mA)	_
M.3.2	Tripping device and monitoring voltage	N/A





EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
M.3.2.1	Conditions for use of a tripping device or a monitoring voltage		N/A
M.3.2.2	Tripping device		N/A
M.3.2.3	Monitoring voltage (V)		N/A
N	ANNEX N, IMPULSE TEST GENERATORS (se 6.2.2.1, 7.3.2, 7.4.3 and Clause G.5)	e 1.5.7.2, 1.5.7.3, 2.10.3.9,	N/A
N.1	ITU-T impulse test generators		N/A
N.2	IEC 60065 impulse test generator		N/A
P	ANNEX P, NORMATIVE REFERENCES		_
Q	ANNEX Q, Voltage dependent resistors (VDR	s) (see 1.5.9.1)	N/A
	a) Preferred climatic categories		N/A
	b) Maximum continuous voltage		N/A
	c) Pulse current		N/A
R	ANNEX R, EXAMPLES OF REQUIREMENTS F PROGRAMMES	FOR QUALITY CONTROL	N/A
R.1	Minimum separation distances for unpopulated coated printed boards (see 2.10.6.2)		N/A
R.2	Reduced clearances (see 2.10.3)		N/A
S	ANNEX S, PROCEDURE FOR IMPULSE TEST	ING (see 6.2.2.3)	N/A
S.1	Test equipment		N/A
S.2	Test procedure		N/A
S.3	Examples of waveforms during impulse testing		N/A
Т	ANNEX T, GUIDANCE ON PROTECTION AGA (see 1.1.2)	INST INGRESS OF WATER	N/A
U	ANNEX U, INSULATED WINDING WIRES FOR INTERLEAVED INSULATION (see 2.10.5.4)	USE WITHOUT	N/A
V	ANNEX V, AC POWER DISTRIBUTION SYSTE	:MS (see 1.6.1)	N/A
V.1	Introduction		N/A
V.2	TN power distribution systems		N/A





	EN 60950-1		
Clause	Requirement + Test	Result - Remark	Verdict
w	ANNEX W, SUMMATION OF TOUCH CURREN	NTS	N/A
W.1	Touch current from electronic circuits		N/A
W.1.1	Floating circuits		N/A
W.1.2	Earthed circuits		N/A
W.2	Interconnection of several equipments		N/A
W.2.1	Isolation		N/A
W.2.2	Common return, isolated from earth		N/A
W.2.3	Common return, connected to protective earth		N/A
X	ANNEX X, MAXIMUM HEATING EFFECT IN TI	RANSFORMER TESTS	P
X.1	Determination of maximum input current		Р
X.2	Overload test procedure		Р
Υ	ANNEX Y, ULTRAVIOLET LIGHT CONDITION	ING TEST (see 4.3.13.3)	N/A
Y.1	Test apparatus		N/A
Y.2	Mounting of test samples		N/A
Y.3	Carbon-arc light-exposure apparatus		N/A
Y.4	Xenon-arc light exposure apparatus		N/A
Z	ANNEX Z, OVERVOLTAGE CATEGORIES (se	e 2.10.3.2 and Clause G.2)	N/A
AA	ANNEX AA, MANDREL TEST (see 2.10.5.8)		N/A
ВВ	ANNEX BB, CHANGES IN THE SECOND EDIT	TION	_
СС	ANNEX CC, EVALUATION OF INTEGRATED CLIMITERS	CIRCUIT (IC) CURRENT	N/A
CC.1	General		N/A
CC.2	Test program 1		N/A
CC.3	Test program 2		N/A
DD	ANNEX DD, REQUIREMENTS FOR THE MOU RACK-MOUNTED EQUIPMENT	NTING MEANS OF	N/A
DD.1	General		N/A
DD.2	Mechanical strength test, variable N		N/A
DD.3	Mechanical strength test, 250N, including end		N/A



Page 29 of 55

Report No.: WJT190524-LVD-B-02

EN 60950-1				
Clause Requirement + Test Result - Remark Verdict				
	stops			
DD.4	Compliance:		N/A	

EE	SHREDDERS	
EE.1		
EE.2	Markings and instructions	N/A
	Use of markings or symbols	N/A
	Information of user instructions, maintenance and/or servicing instructions:	N/A
EE.3	Inadvertent reactivation test	N/A
EE.4	Disconnection of power to hazardous moving parts:	N/A
	Use of markings or symbols	N/A
EE.5	Protection against hazardous moving parts	N/A
	Test with test finger (Figure 2A):	N/A
	Test with wedge probe (Figure EE1 and EE2) :	N/A

ATTACHMENT TO TEST REPORT IEC 60950-1 EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES

Information technology equipment - Safety -

Part 1: General requirements

Differences according to..... EN 60950-1:2006/A11:2009/A1:2010/A12:2011/A2:2013

EU GD IEC60950 1B II Attachment Form No.....:

Attachment Originator..... SGS Fimko Ltd

Master Attachment.....: Date 2013-09

Copyright © 2011 IEC System for Conformity Testing and Certification of Electrical Equipment

(IECEE), Geneva, Switzerland. All rights reserved.

EN 60950-1:2006/A11:2009/A1:2010/A12:2011/A2:2013 - CENELEC COMMON MODIFICATIONS

	IEC 60950-1, GROUP DIFFER	ENCES (CENELEC common modifications EN)	
Clause	Requirement + Test	Result - Remark	Verdict
	Clauses, subclauses, notes, IEC60950-1 and it's amendr	tables and figures which are additional to those in mets are prefixed "Z"	
Contents	Add the following annexes:		N/A
	Annex ZA (normative)	Normative references to international publications with their	
	corresponding European	publications	
(A2:2013)	Annex ZB (normative) Annex ZD (informative)	Special national conditions IEC and CENELEC code designations for flexible cords	





EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

	IEC 60950-1, GROUP DIFFERENCES (CENELEC common modifications EN)	
Clause	Requirement + Test Result - Remark	Verdict
General	Delete all the "country" notes in the reference document (IEC 60950-1:2005) according to the following list: 1.4.8 Note 2 1.5.1 Note 2 & 3 1.5.7.1 Note 1.5.8 Note 2 1.5.9.4 Note 1.7.2.1 Note 4, 5 & 6 2.2.3 Note 2.2.4 Note 2.3.2 Note 2.3.2.1 Note 2 2.3.4 Note 2 2.6.3.3 Note 2 & 3 2.7.1 Note 2.10.3.2 Note 2 2.10.5.13 Note 3 3.2.1.1 Note 3.2.4 Note 3.2.5.1 Note 2 4.3.6 Note 1 & 2 4.7 Note 4 4.7.2.2 Note 4.7.3.1Note 2 5.1.7.1 Note 3 & 4 5.3.7 Note 1	N/A
	6 Note 2 & 5 6.1.2.1 Note 2 6.1.2.2 Note 6.2.2 Note 6.2.2.1 Note 2 6.2.2.2 Note 7.1 Note 3 7.2 Note 7.3 Note 1 & 2 G.2.1 Note 2 Annex H Note 2	
General (A1:2010)	Delete all the "country" notes in the reference document (IEC 60950-1:2005/A1:2010) according to the following list: 1.5.7.1 Note 6.1.2.1 Note 2	N/A
General (A2:2013)	Delete all the "country" notes in the reference document (IEC 60950-1:2005/A2:2013) according to the following list: 2.7.1 Note * 2.10.3.1 Note 2 6.2.2. Note * Note of secretary: Text of Common Modification remains unchanged.	N/A
1.3.Z1	Add the following subclause: 1.3.Z1 Exposure to excessive sound pressure The apparatus shall be so designed and constructed as to present no danger when used for its intended purpose, either in normal operating conditions or under fault conditions, particularly providing protection against exposure to excessive sound pressures from headphones or earphones. NOTE Z1 A new method of measurement is described in EN 50332-1, Sound system equipment: Headphones and earphones associated with portable audio equipment - Maximum sound pressure level measurement methodology and limit considerations - Part 1: General method for "one package equipment: Headphones and earphones associated with portable audio equipment - Maximum sound pressure level measurement methodology and limit considerations - Part 2: Guidelines to associate sets with headphones	N/A
(A12:2011)	coming from different manufacturers. In EN 60950-1:2006/A12:2011 Delete the addition of 1.3.Z1 / EN 60950-1:2006 Delete the definition 1.2.3.Z1 / EN 60950-1:2006 /A1:2010	N/A



Page 31 of 55 Report No.: WJT190524-LVD-B-02

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

	IEC 60950-1, GROUP DIFFERENCES (CENELEC c	ommon modifications EN)	
Clause	Requirement + Test	Result - Remark	Verdict
1.5.1	Add the following NOTE: NOTE Z1 The use of certain substances in electrical and electronic equipment is restricted within the EU: see Directive 2002/95/EC		N/A
1.7.2.1 (A1:2010)	In addition, for a PORTABLE SOUND SYSTEM, the instructions shall include a warning that excessive sound pressure from earphones and headphones can cause hearing loss.		N/A
1.7.2.1 (A12.2011)	In EN 60950-1:2006/A12:2011 Delete NOTE Z1 and the addition for Portable Sound System. Add the following clause and annex to the existing standard and amendments.		N/A
	Zx Protection against excessive sound pres music players	ssure from personal	N/A





EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

	IEC 60950-1, GROUP DIFFERENCES (CENELEC c		
Clause	Requirement + Test	Result - Remark	Verdict
	Zx.1 General This sub-clause specifies requirements for protection against excessive sound pressure from personal music players that are closely coupled to the ear. It also specifies requirements for earphones and headphones intended for use with personal music players.		N/A
	A personal music player is a portable equipment for personal use, that: is designed to allow the user to listen to recorded or broadcast sound or video; and primarily uses headphones or earphones that can be worn in or on or around the ears; and allows the user to walk around while in use. NOTE 1 Examples are hand-held or body-worn portable CD players, MP3 audio players, mobile phones with MP3 type features, PDA's or similar equipment.		
	A personal music player and earphones or headphones intended to be used with personal music players shall comply with the requirements of this sub-clause.		
	The requirements in this sub-clause are valid for music or video mode only.		
	The requirements do not apply: while the personal music player is connected to an external amplifier; or while the headphones or earphones are not used. NOTE 2 An external amplifier is an amplifier which is not part of the personal music player or the listening device, but which is intended to play the music as a standalone music player.		
	The requirements do not apply to: hearing aid equipment and professional equipment; NOTE 3 Professional equipment is equipment sold through special sales channels. All products sold through normal electronics stores are considered not to be professional equipment.		
	analogue personal music players (personal music players without any kind of digital processing of the sound signal) that are brought to the market before the end of 2015. NOTE 4 This exemption has been allowed because this technology is falling out of use and it is expected that within a few years it will no longer exist. This exemption will not be extended to other technologies.		N/A
	For equipment which is clearly designed or intended for use by young children, the limits of EN 71-1 apply.		



Page 33 of 55 Report No.: WJT190524-LVD-B-02

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

Clause	Requirement + Test	Result - Remark	Verdict
	Zx.2 Equipment requirements No safety provision is required for equipment that complies with the following: equipment provided as a package (personal music player with its listening device), where the acoustic output LAeq, T is ≤ 85 dBA measured while playing the fixed "programme simulation noise" as described in EN 50332-1; and a personal music player provided with an analogue electrical output socket for a listening device, where the electrical output is ≤ 27 mV measured as described in EN 50332-2, while playing the fixed "programme simulation noise" as described in EN 50332-1. NOTE 1 Wherever the term acoustic output is used in this clause, the 30 s A-weighted equivalent sound pressure level LAeq, T is meant. See also Zx.5 and Annex Zx.		N/A
	All other equipment shall: a) protect the user from unintentional acoustic outputs exceeding those mentioned above; and b) have a standard acoustic output level not exceeding those mentioned above, and automatically return to an output level not exceeding those mentioned above when the power is switched off; and		





EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

Clause	Requirement + Test	Result - Remark	Verdict
Jause	c) provide a means to actively inform the user of the increased sound pressure when the equipment is operated with an acoustic output exceeding those mentioned above. Any means used shall be acknowledged by the user before activating a mode of operation which allows for an acoustic output exceeding those mentioned above. The acknowledgement does not need to be repeated more than once every 20 h of cumulative listening time; and NOTE 2 Examples of means include visual or audible signals. Action from the user is always required. NOTE 3 The 20 h listening time is the accumulative listening time, independent how often and how long the personal music player has been switched off. d) have a warning as specified in Zx.3; and e) not exceed the following: 1) equipment provided as a package (player with Its listening device), the acoustic output shall be ≤ 100 dBA measured while playing the fixed "programme simulation noise" described in EN 50332-1; and 2) a personal music player provided with an analogue electrical output socket for a listening device, the electrical output shall be ≤ 150 mV measured as described in EN 50332-2, while playing the fixed "programme simulation noise" described in EN 50332-1.		N/A
	For music where the average sound pressure (long term LAeq,T) measured over the duration of the song is lower than the average produced by the programme simulation noise, the warning does not need to be given as long as the average sound pressure of the song is below the basic limit of 85 dBA. In this case T becomes the duration of the song. NOTE 4 Classical music typically has an average sound pressure (long term LAeq,T) which is much lower than the average programme simulation noise. Therefore, if the player is capable to analyse the song and compare it with the programme simulation noise, the warning does not need to be given as long as the average sound pressure of the song is below the basic limit of 85 dBA. For example, if the player is set with the programme simulation noise to 85 dBA, but the average music level of the song is only 65 dBA, there is no need to give a warning or ask an acknowledgement as long as the average sound level of the song is not above the basic limit of 85 dBA.		





EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

Clause	Requirement + Test	Result - Remark	Verdict
	Zx.3 Warning The warning shall be placed on the equipment, or on the packaging, or in the instruction manual and shall consist of the following: the symbol of Figure 1 with a minimum height of 5 mm; and the following wording, or similar:		N/A
	"To prevent possible hearing damage, do not listen at high volume levels for long periods." Figure 1 – Warning label (IEC 60417-6044) Alternatively, the entire warning may be given through the equipment display during use, when the user is asked to acknowledge activation of the higher level.		
	Zx.4 Requirements for listening devices (headp	hones and earphones)	N/A
	Zx.4.1 Wired listening devices with analogue input With 94 dBA sound pressure output LAeq,T, the input voltage of the fixed "programme simulation noise" described in EN 50332-2 shall be ≥ 75 mV. This requirement is applicable in any mode where the headphones can operate (active or		N/A
	passive), including any available setting (for example built-in volume level control). NOTE The values of 94 dBA – 75 mV correspond with 85dBA – 27 mV and 100 dBA – 150 mV.		



Page 36 of 55 Report No.: WJT190524-LVD-B-02

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

Clause	Requirement + Test	Result - Remark	Verdict
	Zx.4.2 Wired listening devices with digital input With any playing device playing the fixed "programme simulation noise" described in EN 50332-1 (and respecting the digital interface standards, where a digital interface standard exists that specifies the equivalent acoustic level), the acoustic output LAeq,T of the listening device shall be ≤ 100 dBA.		N/A
	This requirement is applicable in any mode where the headphones can operate, including any available setting (for example built-in volume level control, additional sound feature like equalization, etc.).		
	NOTE An example of a wired listening device with digital input is a USB headphone.		
	In wireless mode: with any playing and transmitting device playing the fixed programme simulation noise described in EN 50332-1; and respecting the wireless transmission standards, where an air interface standard exists that specifies the equivalent acoustic level; and with volume and sound settings in the listening device (for example built-in volume level control, additional sound feature like equalization, etc.) set to the combination of positions that maximize the measured acoustic output for the abovementioned programme simulation noise, the acoustic output LAeq,T of the listening device shall be ≤ 100 dBA. NOTE An example of a wireless listening device is a Bluetooth headphone.		N/A
	Zx.5 Measurement methods Measurements shall be made in accordance with EN 50332-1 or EN 50332-2 as applicable. Unless stated otherwise, the time interval T shall be 30 s.		N/A
	NOTE Test method for wireless equipment provided without listening device should be defined.		





 EN 60950-1

 Clause
 Requirement + Test
 Result - Remark
 Verdict

	IEC 60950-1, GROUP DIFFERENCES (CENELEC c	ommon modifications EN)	
Clause	Requirement + Test	Result - Remark	Verdict
2.7.1	Replace the subclause as follows:		Р
	Basic requirements		
	To protect against excessive current, short-circuits and earth faults in PRIMARY CIRCUITS, protective devices shall be included either as integral parts of the equipment or as parts of the building installation, subject to the following, a), b) and c):		
	a) except as detailed in b) and c), protective devices necessary to comply with the requirements of 5.3 shall be included as parts of the equipment;		
	b) for components in series with the mains input to the equipment such as the supply cord, appliance coupler, r.f.i. filter and switch, short-circuit and earth fault protection may be provided by protective devices in the building installation;		
	c) it is permitted for PLUGGABLE EQUIPMENT TYPE B or PERMANENTLY CONNECTED EQUIPMENT, to rely on dedicated overcurrent and short-circuit protection in the building installation, provided that the means of protection, e.g. fuses or circuit breakers, is fully specified in the installation instructions.		N/A
	If reliance is placed on protection in the building installation, the installation instructions shall so state, except that for PLUGGABLE EQUIPMENT TYPE A the building installation shall be regarded as providing protection in accordance with the rating of the wall socket outlet.		
2.7.2	This subclause has been declared 'void'.		N/A
3.2.3	Delete the NOTE in Table 3A, and delete also in this table the conduit sizes in parentheses.		N/A
3.2.5.1	Replace "60245 IEC 53" by "H05 RR-F"; "60227 IEC 52" by "H03 VV-F or H03 VVH2-F"; "60227 IEC 53" by "H05 VV-F or H05 VVH2-F2".		N/A
	In Table 3B, replace the first four lines by the following:		
	Up to and including 6 0,75 a) Over 6 up to and including 10 (0,75) b) 1,0 Over 10 up to and including 16 (1,0) c) 1,5		
	In the conditions applicable to Table 3B delete the words "in some countries" in condition ^{a)} .		
	In NOTE 1, applicable to Table 3B, delete the second sentence.		



Requirement + Test

Clause

Page 38 of 55

EN 60950-1		
	Result - Remark	Verdict

Report No.: WJT190524-LVD-B-02

Clause	Requirement + Test	Result - Remark	Verdict
3.2.5.1 (A2:2013)	NOTE Z1 The harmonised code designations corresponding to the IEC cord types are given in Annex ZD		N/A
3.3.4	In Table 3D, delete the fourth line: conductor sizes for 10 to 13 A, and replace with the following:		N/A
	Over 10 up to and including 16 1,5 to 2,5 1,5 to 4		
	Delete the fifth line: conductor sizes for 13 to 16 A		
4.3.13.6	Replace the existing NOTE by the following:		N/A
(A1:2010)	NOTE Z1 Attention is drawn to:		
	1999/519/EC: Council Recommendation on the limitation of exposure of the general public to electromagnetic fields 0 Hz to 300 GHz, and		
	2006/25/EC: Directive on the minimum health and safety requirements regarding the exposure of workers to risks arising from physical agents (artifical optical radiation).		
	Standards taking into account mentioned Recommendation and Directive which demonstrate compliance with the applicable EU Directive are indicated in the OJEC.		N/A
Annex H	Replace the last paragraph of this annex by:		N/A
	At any point 10 cm from the surface of the OPERATOR ACCESS AREA, the dose rate shall not exceed 1 µSv/h (0,1 mR/h) (see NOTE). Account is taken of the background level.		
	Replace the notes as follows:		
	NOTE These values appear in Directive 96/29/Euratom.		
	Delete NOTE 2.		
Bibliography	Additional EN standards.		

ZA	NORMATIVE REFERENCES TO INTERNATIONAL PUBLICATIONS	N/A
	WITH THEIR CORRESPONDING EUROPEAN PUBLICATIONS	

	ZB ANNEX (normative) SPECIAL NATIONAL CONDITIONS (EN)			
Clause	Requirement + Test	Result - Remark	Verdict	
1.2.4.1	In Denmark , certain types of Class I appliances (see 3.2.1.1) may be provided with a plug not establishing earthing conditions when inserted into Danish socket-outlets.		N/A	
1.2.13.14	In Norway and Sweden , for requirements see 1.7.2.1 and 7.3 of this annex.		N/A	



Page 39 of 55

	EN 60950-1		
Clause	Requirement + Test	Result - Remark	Verdict

	ZB ANNEX (normative)				
	SPECIAL NATIONAL CONDITIONAL	ONS (EN)			
Clause	Requirement + Test	Result - Remark	Verdict		
1.5.7.1	In Finland, Norway and Sweden , resistors bridging BASIC INSULATION in CLASS I PLUGGABLE EQUIPMENT TYPE A must comply with the requirements in 1.5.7.1. In addition when a single resistor is used, the resistor must withstand the resistor test in 1.5.7.2.		N/A		
1.5.8	In Norway , due to the IT power system used (see annex V, Figure V.7), capacitors are required to be rated for the applicable line-to-line voltage (230 V).		N/A		
1.5.9.4	In Finland , Norway and Sweden , the third dashed sentence is applicable only to equipment as defined in 6.1.2.2 of this annex.		N/A		





EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

	ZB ANNEX (normative))	
Ola de	SPECIAL NATIONAL CONDITIONAL C		Ar. aba
1.7.2.1	Requirement + Test In Finland, Norway and Sweden, CLASS I	Result - Remark	Verdict N/A
	PLUGGABLE EQUIPMENT TYPE A intended for connection to other equipment or a network shall, if safety relies on connection to protective earth or if surge suppressors are connected between the network terminals and accessible parts, have a marking stating that the equipment must be connected to an earthed mains socket-outlet.		
	The marking text in the applicable countries shall be as follows:		
	In Finland: "Laite on liitettävä suojakoskettimilla varustettuun pistorasiaan"		
	In Norway: "Apparatet må tilkoples jordet stikkontakt"		
	In Sweden: "Apparaten skall anslutas till jordat uttag"		
	In Norway and Sweden , the screen of the cable distribution system is normally not earthed at the entrance of the building and there is normally no equipotential bonding system within the building. Therefore the protective earthing of the building installation need to be isolated from the screen of a cable distribution system.		
	It is however accepted to provide the insulation external to the equipment by an adapter or an interconnection cable with galvanic isolator, which may be provided by e.g. a retailer.		
	The user manual shall then have the following or similar information in Norwegian and Swedish language respectively, depending on in what country the equipment is intended to be used in:		
	"Equipment connected to the protective earthing of the building installation through the mains connection or through other equipment with a connection to protective earthing – and to a cable distribution system using coaxial cable, may in some circumstances create a fire hazard. Connection to a cable distribution system has therefore to be provided through a device providing electrical isolation below a certain frequency range (galvanic isolator, see EN 60728-11)."		



WJT


Page 41 of 55 Report No.: WJT190524-LVD-B-02

	EN 60950-1			
Clause	Requirement + Test		Result - Remark	Verdict

	ZB ANNEX (normative)		
	SPECIAL NATIONAL CONDITIONAL	ONS (EN)	
Clause	Requirement + Test	Result - Remark	Verdict
	NOTE In Norway, due to regulation for installations of cable distribution systems, and in Sweden, a galvanic isolator shall provide electrical insulation below 5 MHz. The insulation shall withstand a dielectric strength of 1,5 kV r.m.s., 50 Hz or 60 Hz, for 1 min.		N/A
	Translation to Norwegian (the Swedish text will also be accepted in Norway):		
	"Utstyr som er koplet til beskyttelsesjord via nettplugg og/eller via annet jordtilkoplet utstyr – og er tilkoplet et kabel-TV nett, kan forårsake brannfare. For å unngå dette skal det ved tilkopling av utstyret til kabel-TV nettet installeres en galvanisk isolator mellom utstyret og kabel- TV nettet."		
	Translation to Swedish:		
	"Utrustning som är kopplad till skyddsjord via jordat vägguttag och/eller via annan utrustning och samtidigt är kopplad till kabel-TV nät kan i vissa fall medföra risk för brand. För att undvika detta skall vid anslutning av utrustningen till kabel-TV nät galvanisk isolator finnas mellan utrustningen och kabel-TV nätet."		
1.7.2.1 (A2:2013)	In Denmark , CLASS I PLUGGABLE EQUIPMENT TYPE A intended for connection to other equipment or a network shall, if safety relies on connection to protective earth or if surge suppressors are connected between the network terminals and accessible parts, have a marking stating that the equipment must be connected to an earthed mains socket-outlet. The marking text in Denmark shall be as follows: In Denmark : "Apparatets stikprop skal tilsluttes en stikkontakt med jord, som giver forbindelse til stikproppens jord."		N/A
1.7.5	In Denmark , socket-outlets for providing power to other equipment shall be in accordance with the Heavy Current Regulations, Section 107-2-D1, Standard Sheet DK 1-3a, DK 1-5a or DK 1-7a, when used on Class I equipment. For STATIONARY EQUIPMENT the socket-outlet shall be in accordance with Standard Sheet DK 1-1b or DK 1-5a.		N/A
	For CLASS II EQUIPMENT the socket outlet shall be in accordance with Standard Sheet DKA 1-4a.		







	ZB ANNEX (normative))	
	SPECIAL NATIONAL CONDITIONAL	ONS (EN)	
Clause	Requirement + Test	Result - Remark	Verdict
1.7.5 (A2:2013)	In Denmark , socket-outlets for providing power to other equipment shall be in accordance with the DS 60884-2-D1:2011. For class I equipment the following Standard Sheets are applicable: DK 1-3a, DK 1-1c, DK 1-1d, DK 1-5a or DK 1-7a, with the exception for STATIONARY EQUIPMENT where the socket-outlets shall be in accordance with Standard Sheet DK 1-1b, DK 1-1c, DK 1-1d or DK 1-5a. Socket outlets intended for providing power to Class II apparatus with a rated current of 2,5 A shall be in accordance with DS 60884-2-D1 standard sheet DKA 1-4a. Other current rating socket outlets shall be in compliance with by DS 60884-2-D1 Standard Sheet DKA 1-3a or DKA 1-3b. Justification the Heavy Current Regulations, 6c	No socket-outlet provided.	N/A
2.2.4	In Norway , for requirements see 1.7.2.1, 6.1.2.1 and 6.1.2.2 of this annex.		N/A
2.3.2	In Finland , Norway and Sweden there are additional requirements for the insulation. See 6.1.2.1 and 6.1.2.2 of this annex.		N/A
2.3.4	In Norway , for requirements see 1.7.2.1, 6.1.2.1 and 6.1.2.2 of this annex.		N/A
2.6.3.3	In the United Kingdom , the current rating of the circuit shall be taken as 13 A, not 16 A.		N/A
2.7.1	In the United Kingdom , to protect against excessive currents and short-circuits in the PRIMARY CIRCUIT of DIRECT PLUG-IN EQUIPMENT, tests according to 5.3 shall be conducted, using an external protective device rated 30 A or 32 A. If these tests fail, suitable protective devices shall be included as integral parts of the DIRECT PLUG-IN EQUIPMENT, so that the requirements of 5.3 are met.		N/A
2.10.5.13	In Finland , Norway and Sweden , there are additional requirements for the insulation, see 6.1.2.1 and 6.1.2.2 of this annex.		N/A
3.2.1.1	In Switzerland , supply cords of equipment having a RATED CURRENT not exceeding 10 A shall be provided with a plug complying with SEV 1011 or IEC 60884-1 and one of the following dimension sheets: SEV 6532-2.1991 Plug Type 15 3P+N+PE 250/400 V, 10 A		N/A



Page 43 of 55 Report No.: WJT190524-LVD-B-02

EN 60950-1				
Clause	Requirement + Test	Result - Remark	Verdict	

	2	ZB ANNEX (n	ormative)		
	SPECIAL	NATIONAL	CONDITIO	ONS (EN)	
Clause	Requirement + Test			Result - Remark	Verdict
	250 V, 10 A	ug Type 11 ug Type 12	L+N L+N+PE		N/A
	In general, EN 60309 applie exceeding 10 A. However, socket-outlet system is bei Switzerland, the plugs of withe following dimension shipsets and the following the following dimension shipsets are selected by 1998: SEV 5932-2.1998: Plug Ty 230/400 V, 16 A	a 16 Å plug a ng introduced thich are acco eets, publishe tpe 25, 3L+N	and I in ording to ed in +PE		
	SEV 5934-2.1998: Plug Ty	pe 23, L+N+F	PE 250 V,		
3.2.1.1	In Denmark , supply cords equipment having a rated of exceeding 13 A shall be proaccording to the Heavy Cu Section 107-2-D1.	of single-pha current not ovided with a	se plug		N/A
	CLASS I EQUIPMENT pro socket-outlets with earth co intended to be used in loca against indirect contact is r the wiring rules shall be pro accordance with standard 2-5a.	ontacts or whi ations where prequired acco ovided with a	orotection rding to plug in		
	If poly-phase equipment ar equipment having a RATE exceeding 13 A is provided a plug, this plug shall be in Heavy Current Regulations EN 60309-2.	D CURRENT with a supply accordance	cord with		





	EN 60	950-1	
Clause	Requirement + Test	Result - Remark	Verdict

	ZB ANNEX (normative))	
	SPECIAL NATIONAL CONDITIONAL	ONS (EN)	
Clause	Requirement + Test	Result - Remark	Verdict
3.2.1.1 (A2:2013)	In Denmark , supply cords of single-phase equipment having a rated current not exceeding 13 A shall be provided with a plug according to DS 60884-2-D1. CLASS I EQUIPMENT provided with socket-outlets with earth contacts or which are intended to be used in locations where protection against indirect contact is required according to the wiring rules shall be provided with a plug in accordance with standard sheet DK 2-1a or DK 2-5a. If a single-phase equipment having a RATED CURRENT exceeding 13 A or if a poly-phase equipment is provided with a supply cord with a plug, this plug shall be in accordance with the standard sheets DK 6-1a in DS 60884-2-D1 or EN 60309-2. Justification the Heavy Current Regulations, 6c		N/A
3.2.1.1	In Spain , supply cords of single-phase equipment having a rated current not exceeding 10 A shall be provided with a plug according to UNE 20315:1994. Supply cords of single-phase equipment having a		N/A
	rated current not exceeding 2,5 A shall be provided with a plug according to UNE-EN 50075:1993.		
	CLASS I EQUIPMENT provided with socket-outlets with earth contacts or which are intended to be used in locations where protection against indirect contact is required according to the wiring rules, shall be provided with a plug in accordance with standard UNE 20315:1994.		
	If poly-phase equipment is provided with a supply cord with a plug, this plug shall be in accordance with UNE-EN 60309-2.		
3.2.1.1	In the United Kingdom , apparatus which is fitted with a flexible cable or cord and is designed to be connected to a mains socket conforming to BS 1363 by means of that flexible cable or cord and plug, shall be fitted with a 'standard plug' in accordance with Statutory Instrument 1768:1994 - The Plugs and Sockets etc. (Safety) Regulations 1994, unless exempted by those regulations.		N/A
	NOTE 'Standard plug' is defined in SI 1768:1994 and essentially means an approved plug conforming to BS 1363 or an approved conversion plug.		





		EN 60950-1	
Clause	Requirement + Test	Result - Remark	Verdict

	ZB ANNEX (normative)		
	SPECIAL NATIONAL CONDITION	ONS (EN)	
Clause	Requirement + Test	Result - Remark	Verdict
3.2.1.1	In Ireland , apparatus which is fitted with a flexible cable or cord and is designed to be connected to a mains socket conforming to I.S. 411 by means of that flexible cable or cord and plug, shall be fitted with a 13 A plug in accordance with Statutory Instrument 525:1997 - National Standards Authority of Ireland (section 28) (13 A Plugs and Conversion Adaptors for Domestic Use) Regulations 1997.		N/A
3.2.4	In Switzerland , for requirements see 3.2.1.1 of this annex.		N/A
3.2.5.1	In the United Kingdom , a power supply cord with conductor of 1,25 mm2 is allowed for equipment with a rated current over 10 A and up to and including 13 A.		N/A
3.3.4	In the United Kingdom , the range of conductor sizes of flexible cords to be accepted by terminals for equipment with a RATED CURRENT of over 10 A up to and including 13 A is: • 1,25 mm² to 1,5 mm² nominal cross-sectional		N/A
	area.		
4.3.6	In the United Kingdom , the torque test is performed using a socket outlet complying with BS 1363 part 1:1995, including Amendment 1:1997 and Amendment 2:2003 and the plug part of DIRECT PLUG-IN EQUIPMENT shall be assessed to BS 1363: Part 1, 12.1, 12.2, 12.3, 12.9, 12.11, 12.12, 12.13, 12.16 and 12.17, except that the test of 12.17 is performed at not less than 125 °C. Where the metal earth pin is replaced by an Insulated Shutter Opening Device (ISOD), the requirements of clauses 22.2 and 23 also apply.		N/A
4.3.6	In Ireland , DIRECT PLUG-IN EQUIPMENT is known as plug similar devices. Such devices shall comply with Statutory Instrument 526:1997 - National Standards Authority of Ireland (Section 28) (Electrical plugs, plug similar devices and sockets for domestic use) Regulations, 1997.		N/A





EN 60950-1				
Clause	Requirement + Test	Result - Remark	Verdict	

	ZB ANNEX (normative))	
	SPECIAL NATIONAL CONDITION	ONS (EN)	
Clause	Requirement + Test	Result - Remark	Verdict
5.1.7.1	In Finland , Norway and Sweden TOUCH CURRENT measurement results exceeding 3,5 mA r.m.s. are permitted only for the following equipment:		N/A
	STATIONARY PLUGGABLE EQUIPMENT TYPE A that is intended to be used in a RESTRICTED ACCESS LOCATION where equipotential bonding has been applied, for example, in a telecommunication centre; and has provision for a permanently connected PROTECTIVE EARTHING CONDUCTOR; and is provided with instructions for the installation of that conductor by a SERVICE PERSON; STATIONARY PLUGGABLE EQUIPMENT TYPE B;		
	• STATIONARY PERMANENTLY CONNECTED EQUIPMENT.		
6.1.2.1 (A1:2010)	In Finland , Norway and Sweden , add the following text between the first and second paragraph of the compliance clause:		N/A
	If this insulation is solid, including insulation forming part of a component, it shall at least consist of either		
	 two layers of thin sheet material, each of which shall pass the electric strength test below, or 		
	- one layer having a distance through insulation of at least 0,4 mm, which shall pass the electric strength test below.		
	Alternatively for components, there is no distance through insulation requirements for the insulation consisting of an insulating compound completely filling the casing, so that CLEARANCES and CREEPAGE DISTANCES do not exist, if the component passes the electric strength test in accordance with the compliance clause below and in addition		
	- passes the tests and inspection criteria of 2.10.11 with an electric strength test of 1,5 kV multiplied by 1,6 (the electric strength test of		
	2.10.10 shall be performed using 1,5 kV), and		
	- is subject to ROUTINE TESTING for electric strength during manufacturing, using a test voltage of 1,5 kV.		





EN 60950-1				
Clause	Requirement + Test	Result - Remark	Verdict	

	ZB ANNEX (normative))	
	SPECIAL NATIONAL CONDITIONAL	ONS (EN)	
Clause	Requirement + Test	Result - Remark	Verdict
	It is permitted to bridge this insulation with an optocoupler complying with 2.10.5.4 b).		N/A
	It is permitted to bridge this insulation with a capacitor complying with EN 60384-14:2005, subclass Y2.		
	A capacitor classified Y3 according to EN 60384-14:2005, may bridge this insulation under the following conditions:		
	- the insulation requirements are satisfied by having a capacitor classified Y3 as defined by EN 60384-14, which in addition to the Y3 testing, is tested with an impulse test of 2,5 kV defined in EN 60950-1:2006, 6.2.2.1;		
	- the additional testing shall be performed on all the test specimens as described in EN 60384-14:		
	- the impulse test of 2,5 kV is to be performed before the endurance test in EN 60384-14, in the sequence of tests as described in EN 60384-14.		
6.1.2.2	In Finland, Norway and Sweden, the exclusions are applicable for PERMANENTLY CONNECTED EQUIPMENT, PLUGGABLE EQUIPMENT TYPE B and equipment intended to be used in a RESTRICTED ACCESS LOCATION where equipotential bonding has been applied, e.g. in a telecommunication centre, and which has provision for a permanently connected PROTECTIVE EARTHING CONDUCTOR and is provided with instructions for the installation of that conductor by a SERVICE PERSON.		N/A
7.2	In Finland , Norway and Sweden , for requirements see 6.1.2.1 and 6.1.2.2 of this annex. The term TELECOMMUNICATION NETWORK in 6.1.2 being replaced by the term CABLE DISTRIBUTION SYSTEM.		N/A
7.3	In Norway and Sweden , for requirements see 1.2.13.14 and 1.7.2.1 of this annex.		N/A
7.3	In Norway , for installation conditions see EN 60728-11:2005.		N/A





1.5.1 **TABLE: List of Critical Components** Ρ Object/Part Manufacturer/ Type/Model **Technical Data** Standard Mark(s) of Trademark No. (Edition / Year) Conformity¹) Various Various 8Ω,1/2W motor UL 60127-1 UL UL 60127-3 Various Various charger **UL 758** UL Input: 100-240VAC,50/60H z,2.0A Output: 29.4V/1.5A Jyh Chung 2200pF, Y1 type, controller JD EN 60384-14 VDE Electronic Co., Ltd. 40//125/21/C 137027 LED light Everlight 817 B Int. Cr / Ext. Cr / Dti. EN 60747-5-5 VDE Electronics Co., 6,5 / 7,7 / 0,45 mm 40027411 Ltd. 50/100/21 Dongguan City battery BH24S1.25A EN 60950-1 Tested with Class B Powerhome appliance Electronic Technology Co., Ltd. PCB UL E123995 **KINGBOARD** KB-5150 **UL 94** V-0. 130°C **LAMINATES HOLDINGS LTD** Supplementary Information:





Page 49 of 55

1.6.2	TABLE: Electrical Data (in Normal Conditions)						Р
U (V~)	I (A)	Irated (A)	P (W)	Fuse #	Ifuse (A)	Conditi	on/Status
90V/50Hz	0.26		12.16	F1	0.26		
90V/60Hz	0.25		12.15	F1	0.25	Normal load	: 5Vdc, 1A
100V/50Hz	0.23	0.5	12.14	F1	0.23		
100V/60Hz	0.22	0.5	12.12	F1	0.22		
240V/50Hz	0.11	0.5	12.14	F1	0.11		
240V/60Hz	0.12	0.5	12.11	F1	0.12		
264V/50Hz	0.09		12.09	F1	0.09		
264V/60Hz	0.09		12.08	F1	0.09		
Supplementa	ry Information	:		•	•	•	

2.1.1.7 TABLE: discharge test							
Condition		V ₀ (V pk)	37%V ₀ (V pk)	37% t (ms)	tu→1s (V pk)		
Supplementary Information:							

2.6.3.4 TABLE: ground continue test						
Location		Resistance measured (mΩ)	Commen	ts		
Supplementary Information:						

2.10.3 and TABLE: 2.10.4	TABLE: Clearance and Creepage Distance Measurements								
Clearance (cl) and creepage distance (cr) at/of/between:	U peak (V)	U r.m.s. (V)	Required cl (mm)	cl (mm)	Required cr (mm)	cr (mm)			
L and N before fuse	420	250	2.0	3.6	2.5	3.6			
Different polarities of fuse	420	250	2.0	3.2	2.5	3.2			
Y cap. primary trace to secondary trace	364	212	2.0	3.4	2.5	3.4			
Optocoupler	372	232	4.0	6.6	5.0	6.6			
T1 primary to seconda	ry 484	258	4.1	>8	5.2	>8			
T1 core to secondary	484	258	4.1	>8	5.2	>8			
Supplementary Informa	Supplementary Information:								





Page 50 of 55

2.10.5	TABLE: Distance Throu	Р					
Distance through insulation (DTI) at/of:		U peak (V)	U rms (V)	Test voltage (V)	Require d DTI (mm)	DTI (mm)	
Enclosure		< 420	< 250	3000	0.4	1.5mm	
Bobbin		484	258	3000	0.4	0.45mm min	
Optocoupler		372	232	3000	0.4	≥0.4mm	
Supplementary Information: No flash over or insulation breakdown after test.							

4.3.8	TABLE	: Batteri	es							N/A	
The tests of 4.3. data is not availa		olicable o	only when approp	oriate batt	ery					N/A	
Is it possible to i	nstall the	battery i	n a reverse pola	rity position	on?					N/A	
	Non-r	echarge	able batteries				Rechargea	able batteri	es		
	Discharging Un-intentiona I charging				ging		Disch	arging		Reversed charging	
Max. current during normal condition						-					
Max. current during fault condition						-					
Test Results:										Verdict	
- Chemical Leak	s									N/A	
- Explosion of The Battery							N/A				
- Emission of Flame or Expulsion of Molten Metal							N/A				
- Electric Strength Tests of Equipment After Completion of Tests							N/A				
Supplementary I	nformatio	n:									

4.5	TABLE: Thermal Requirem	nents				Р
	Supply Voltage (V)	90V/60	90V/60Hz 264\			_
	Ambient 1 T _{max} (°C)	23.1	23.1	23.1	23.1	_
	Ambient 2 T _{max} (°C)	24.0	24.0	24.0	24.0	
Maximum Mea	asured Temperature T of	T (°C)				Allowed T _{max} (°C)
		90V / 50 Hz	90V / 60 Hz	264 V / 50 Hz	264 V / 60 Hz	
		Horizontal	Vertical	Horizontal	Vertical	
Plug Holder		48.9	44.7	46.6	50.5	85





Page 51 of 55

Innut Mira							
Input Wire		72.5	71.	.5	61.8	66.7	105
Primary E Cap.	73.8	71.	.5	66.5	69.7	105	
PCB near D2		81.5	80.	.1	66.4	71.7	130
Y-Capacitor		84.4	78.	.6	84.8	90.3	125
T1 Bobbin		97.3	91.	.4	101.3	102.8	Ref.
T1 Winding		98.4	92.	.6	102.8	104.1	110
Optocoupler		77.2	74.	.6	81.4	85.5	100
PCB near D3		90.4	83.	.6	98.4	100.5	130
Secondary E Cap.	77.4	68.	.3	82.7	83.7	105	
Output Wire near C8		64.7	56.	.6	64.8	66.7	80
Enclosure (internal, top; near transfo	ormer)	71.3	65.	.8	73.5	74.5	Ref.
Enclosure (external, top; near transfe	ormer)	61.3	57.3		62.5	63.3	95
Supplementary Information:							
Temperature T of Winding:	t ₁ (°C)	R ₁ (Ω)	t ₂ (°C)	R ₂ (Ω)	T (°C)	Allowe d T _{max} (°C)	Insulation Class
Supplementary Information:				•	·	<u>'</u>	

4.5.5	TABLE: Ball Pressure Test of Thermoplastic Parts					
Allowed impre	ssion diameter (mm)	≤ 2 mm		_		
Part		Test temperature (°C)				
External enclo	sure	125	125			
Bobbin		125		0.72		
Plug holder		125		0.88		
Supplementary	/ Information:					

5.2	TABLE: Electric Strength Test	Р		
		Voltage shape (AC, DC, impulse, surge)	Test voltage (V)	Breakdown Yes / No
L/N to output ter	minals	AC	3000	No
L/N to enclosure	:	AC	3000	No
Transformer prir	nary to secondary	AC	3000	No
Transformer cor	e to secondary	AC	3000	No
Insulation tape (single layer)		AC	3000	No
Supplementary I	nformation:	1	1	



Page 52 of 55

Report No.: WJT190524-LVD-B-02 5.3 **TABLE: Fault condition tests** P 23.1-23.9 Ambient temperature (°C) Power source for EUT: Manufacturer, model/type. output rating: Fault Supply Fuse # Observation Test Fuse Component voltage time current No. (V) (A) Unit shut down. No damage, no Output 264 10min. 0.02 S-C F1 hazard. Recoverable. When Loaded to 1.43A, unti shut 0.275→ down Temperature refer to the 0.277→ details in tablet of chapter 15. 0.279→ 7hrs. Output o-l 264 F1 Temperature: Winding: 108.8°C; 50min. $0.281 \rightarrow$ Core: 108.4 °C; 0.284→ Enclosure outside: 77.5 °C; 0.019 Ambient: 26.7°C. Unit shut down. No damage. no Secondary hazard. Recoverable. 264 0.02 10min. S-C F1 E cap. Unit shut down. Recoverable. No D3 264 F1 0.01 S-C 10min damage, no hazard.
Unit shut down. No damage, no hazard. Recoverable. Optocoupler 264 0.02 S-C 10min. F1 Pin 1-2 Unit shut down. No damage, no Optocoupler hazard. Recoverable. 10min. 0.02 264 F1 S-C Pin 3-4 Unit shut down. No damage, no Optocoupler hazard. Recoverable. о-с 264 10min. F1 0.02 Pin 1/3 Unit shut down. No damage, no Transformer hazard. Recoverable. 0.02 264 10min. F1 S-C Pin 9-10 Unit shut down. No damage, no Transformer hazard. Recoverable. 264 10min. 0.02 F1 S-C Pin 1-3 Unit shut down. No damage, no hazard. Recoverable. Transformer 264 0.02 S-C 10min. F1 Pin 4-5 Fuse opend immediately, Unrecoverable. No damage, no D2 0 264 5s. F1 S-C hazard. Fuse opend immediately, Primary E Unrecoverable. No damage, no 264 0 S-C 5s. F1

hazard.

Supplementary information:

Cap.

S-C: Short circuit O-C: Open circuit































=====End of Rpeort=====